

EL-RG-25K

2°C~8°C Pharmacy Refrigerator

GENERAL SPECIFICATIONS

| | |
|----------------------|--------------------------------------|
| Cabinet Type | Upright |
| Capacity | 580L / 20.48cu ft |
| Internal Size(W*D*H) | 660×690×1400mm / 25.98×27.17×55.12in |
| External Size(W*D*H) | 780×830×1965mm / 30.71×32.68×77.36in |
| Package Size(W*D*H) | 820×880×2175mm / 32.28×34.65×85.63in |
| NW/GW(Kgs) | 144/173 |

PERFORMANCE

| | |
|---------------------|----------------|
| Temperature Range | 2~8°C |
| Ambient Temperature | 16-32°C |
| Temperature Setting | 5°C |
| Climate Class | N |
| Controller | Microprocessor |
| Display | LED |

REFRIGERATION

| | |
|----------------|--------------------|
| Compressor | 1pc |
| Cooling Method | Forced air cooling |
| Defrost Mode | Automatic |
| Refrigerant | R290 |

CONSTRUCTION

| | |
|--------------------|---|
| External Material | Galvanized steel powder coating (white) |
| Inner Material | Galvanized steel powder coating |
| Shelves | 5/- |
| Castor | Yes |
| Door Lock with Key | Yes |
| Lighting | LED |

ALARM

| | |
|-------------|--|
| Temperature | High/Low temperature,High ambient temperature,Condenser high temperature |
| System | Sensor error,Door ajar, Built-in datalogger USB Failure, Remote alarm |

ELECTRICAL

| | |
|-----------------------------|--------|
| Rated Voltage (V/Hz) | 110/60 |
| Power(W) | 280 |
| Power Consumption (kwh/24h) | 3.3 |

OPTIONS ACCESSORY

| | |
|--------|--|
| System | Power Failure, Foaming/Glass Door, USB Interface, Temperature Recorder |
|--------|--|

